SPECIFICATIONS are found on Turbine Series introduction page.

How to Order -The example below illustrates how the part numbers are constructed. Note - to order a unit with metric threads, specify an asterisk (*) in front of the part number.

500FG	P	12	SS	10
Basic Model 60 GPH. For metal bowl unit see Marine Turbine Series in Section Two.	Water Probe. 1 Add 'P' for an in-bowl water probe. (Omit if not desired).	150 watt Electric Heater: ² Add: '12' for 12 vdc or '24' for 24 vdc (Omit if not desired).	3-piece bracket: Add 'SS' for this bracket option. (Omit if not desired).	Element Filtration Rating. Specify one: '2' for 2 micron '10' for 10 micron or '30' for 30 micron


Must be used with Water Detection Kit -See Accessories Section.


Replacement Service Elements -For all Model 500 Series SERVICE ELEMENT INCLUDES LID SEAL & T-HANDLE O-RING.

20105M-OR	2 Micron (Brown end caps)
	Recommended for Final /Secondary Filtration
2010TM-OR	10 Micron (Blue end caps)
	Recommended for Primary or Secondary Filtration


2010PM-OR 30 Micron (Red end caps)


Recommended for Primary Filtration Only. (A secondary/final filter is required downstream).






Dimension / Mounting Hole Patterns







Performance Graphs These results are from controlled laboratory tests. Field results may vary.



² Recommended for use with Racor Heater Relay Kit -See Accessories Section.

FIGURE 1. 500 Series Cutaway View. The circled number corresponds to the item number shown below.








FIGURE 2. Drain valve configurations. (⁴ Replace with 30488 drain valve)

lte	m/Part No.	Description Case G	ty.
1	RK11888	T-handle (FG/FGSS only), thread is 9/16"-18 SAE	1
	11350	T-handle O-ring (FG)	10
	11003	T-handle Nylon Gasket (FE/FF -not shown)	10
2	RK15078	Lid (FG/FGSS/FGMSS)	1
	15005	Lid Gasket (All models)	10
3	RK15377-01	Body, 3/4"-16 UNF fuel ports (FG, effective 1/15/96)	1
	RK15377-02	Body, 16M X 1.5 fuel ports (metric, effective 1/15/96)	1
	RK15377-03	Body, 3/8"-18 NPTF fuel ports (effective 1/15/96)	1
	RK15082	Body, 9/16"-18 UNF fuel ports (FF/FG)	1
	2010SM-OR	2 Micron Element w/ Seals	12
	2010TM-OR	10 Micron Element w/ Seals	12
	2010PM-OR	30 Micron Element w/ Seals	12
5	RK15310-01	Heater, 12 vdc, 150 watt (for use with body feed-thru)	1
	RK15383-01 ¹	Heater, 12 vdc, 150 watt with body feed-thru (item 8)	1
	RK15310-02	Heater, 24 vdc, 150 watt (for use with body feed-thru)	1
F	RK15383-02 ¹	Heater, 24 vdc, 150 watt with body feed-thru (item 8)	1
	HEATER RETP	OFIT KITS FOR OLDER UNITS: SEE ACCESSORIES	
6	RK15090	Mounting Bracket w/ Attached Bowl Ring (FG)	1
	RK15035	Bowl Ring (FE/FF/FGSS -not shown)	1
7	15374	Bowl Gasket (supercedes 15009 O-ring -All models)	10
8	RK21067	Body Feed-thru Assembly (for bodies with feed-thru po	ort) 1
		(wire gauge = 14 AWG)	
9	RK15013D	Turbine Centrifuge / Conical Baffle (All models)	1
10	RK21069 ²	Water Probe (for bowls with 1/2"-20 UNF port present)	1
	RK20126	Water Probe Port Plug (plastic)	1
11	RK30488	Self-Venting Drain (FF/FG/FGSS, See Figure 2)	10
	11040	Bowl Drain Fitting (FE/FF, See Figure 2)	10
	RK11341	Bowl Drain Gasket Kit (11041 & 11340 -not shown)	10
12	RK15279	See-thru Bowl w/ Water Probe Port & Plug	1
	RK15301	Metal Bowl with 1/4"NPT drain threads (FFM/FGMSS)	1
13	RK15010B	Check Ball w/ Seal (All models)	1
14	RK15081-01 ³	Phillips Head Capscrews 10-24 x 1" (4)	1
	RK15081 ³	Hex/Washer Head Capscrews 10-24 x 7/8" (4)	1
15	RK15079	Standard Return Tube	1
16	RK15300	Mounting Bracket, 3-piece Clamp Type (FGSS/FGM)	1
17	RK15211	Assembly Seal Service Kit, All models (not shown)	1
	RK11746	Seal Service Kit for Drain #11780 (See Figure 2)	1
	15332	Installation Instructions, 500 Series	

¹ Filter body must have port next to fuel Inlet for heater feed-thru installation. In-filter heater kits may require a Heater Relay Kit. Power requirements are (maximum): 12vdc = 12.5 amps, 24vdc = 6.3 amps.

Water probe must be used with a Water Detection Kit.

Models built prior to 2/96 use RK15081-01, after 2/96 use RK15081. (The fuel ports have a 1 1/4" square boss on models made after 2/96). See Accessories Section.